



## Konica 512i 8H Printer

DPI	PASS	SPEED	
480X360	2	240 m <sup>2</sup> /h	
480X720	3	160 m <sup>2</sup> /h	
480X1080	4	120 m <sup>2</sup> /h	
N.W	1000KGS	G.W	1220KGS
Machine Size	4.73*1.07*1.565M		



### Basic Configuration

- BYHX KM512i 8H board
- PhotoPRINT RIP software
- Leadshine 400W AC Servo Motor
- Aluminium beam
- Single THK linear guide with 2 sliders
- 180DPI Encoder stripe with sensor
- Manual screw type carriage lifting system
- Anti collision system
- Unique printhead protection stack
- Suction type waste ink tank
- 36 PCS high precision aluminum made pinch roller
- High quality 225mm wide printing bed
- Adjustable vacuum for printing bed
- LED lights at cleaning position and printing bed
- Negative system
- Individual ink purging system
- Ink supply alarm system
- Low ink warning system
- 4 in 1 Heating control system
- Rear-Printing bed-front heater
- Subtank heater
- 3500W on/off Infrared drying system
- Step-free feeding system
- Basic roll take up
- Keyboard holder

### Premium Configuration

- BYHX KM512i 8H board
- PhotoPRINT RIP software
- Leadshine 400W AC Servo Motor
- Aluminium beam
- Double THK linear guide with 4 sliders
- 180DPI Encoder stripe with sensor
- Manual screw type carriage lifting system
- Anti collision system
- Unique printhead protection stack
- Suction type waste ink tank
- 36 PCS high precision aluminum made pinch roller
- High quality 225mm wide printing bed
- Adjustable vacuum for printing bed
- LED lights at cleaning position and printing bed
- Negative system
- Individual ink purging system
- Ink supply alarm system
- Ink tank alarm system
- Low ink warning system
- 4 in 1 Heating control system
- Rear-Printing bed-front heater
- Subtank heater
- 5500W on/off Infrared drying system
- Step-free feeding system
- Airshaft take up system
- Material holder system
- Double rows feeding
- Double rows take up
- Keyboard holder

